



KS-115FM-V, KS-117FM-V



Web Smart 5/7-Port Fast Ethernet Switches with 1 Fiber Connection

Product Highlights :

- 5/7-port Switch
- Web management
- 4/6 FE 10/100 ports
- 1 FE 100FX port
- Compact design
- 802.1Q Tagged VLAN support
- Fiber connectivity

Key Features :

- Comply with IEEE 802.3 10Base-T and IEEE 802.3u 100Base-TX, 100Base-FX standards
- Provide 4/6 10/100Mbps Fast Ethernet ports and 1 100Base-FX port
- Each TP port supports auto-negotiation and auto-MDI/MDI-X detection
- Support full/half-duplex operation for each TP switched port
- Support a variety of fiber connectors such as ST, SC, MT-RJ, VF-45 and LC
- Multimode and single mode fiber cables (model dependent)
- Self learning for active MAC addresses up to 2K entries
- Store-and-forward switching that only good packets are forwarded
- Forwarding and filtering at full wire speed
- Flow control for traffic congestion
- Broadcast packet storm protection
- Comprehensive LED indicators

Management Features :

- Web-based interface for easy management
- Static IP or DHCP supports for IP configuration
- Port status and configuration
- VLAN configuration
- Security check for management login
- Restore factory default settings
- Remote boot

Specifications :

Number of Ports	KS-115FM-V : 4 x 10/100TX ports with 1 x 100FX port KS-117FM-V : 6 x 10/100TX ports with 1 x 100FX port
TX Port	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX std. Shielded RJ-45 jacks with Auto MDI-X detection Auto-negotiation capable Speed for 10Mbps or 100Mbps Full-duplex or half-duplex operation
FX Port	IEEE 802.3u 100BASE-FX compliant Fixed 100Mbps Full-duplex operation
Flow control	IEEE 802.3x pause packet for full-duplex operation Back pressure for half-duplex operation
Cables	10Base-T : Cat. 3, 4, 5 or higher (100 meters max.) 100Base-TX : Cat. 5, 5e or higher (100 meters max.) 100Base-FX : multimode or single mode fiber cable
LEDs	Power status TX ports : Speed, Link/Act, Duplex/Collision status FX port : Link/Act status, Duplex/Collision status



Ordering Information :

Model KS-115FM-V-X KS-117FM-V-X	Fiber Mode	Connector	Ref. Distance
-VT	MM	Dual ST	2km
-VC	MM	Dual SC	2km
-VJM	MM	MT-RJ	2km
-VVM	MM	VF-45	2km
-VSA2	SM	Dual SC	20km
-VSL2	SM	Dual SC	20km
-VSL3	SM	Dual SC	30km
-VSL4	SM	Dual SC	40km
-VSL6	SM	Dual SC	60km
-VW3515	SM	Bi-Di SC	15~20km
-VW5315	SM	Bi-Di SC	15~20km

MM : Multimode Fiber
SM : Single Mode Fiber

Filtering Rate	14,880 pps for Ethernet (10BASE-T) 148,800 pps for Fast Ethernet (100BASE-TX)
Forwarding Rate	14,880 pps for Ethernet (10BASE-T) 148,800 pps for Fast Ethernet (100BASE-TX)
Filtering Address	Multicast/Broadcast/Unicast address
MAC Address Table	2K entries
Ageing Time	300 seconds
VLAN Mode	Port-based VLAN, 802.1Q Tag-based VLAN
VLAN groups	16 groups (Group 0 ~ 15)
Port PVID	Full 12-bit VID, per port setting
Port Tag Mode	Tag/Untag mode, per port setting
Environment	Operating Temperature : 0°C ~ 40°C Relative Humidity : 10% ~ 90% non-condensing
Dimension	144 x 100 x 26 mm (WxDxH)
DC IN Power	Rating +7.5V min. 1A
Operating Voltage	+6.5V ~ +12.5VDC (Device DC Input)
Power Consumption	7 watts. (max.)

Fiber Optical Specification :

Model	Connector	FiberCable	Wavelength	Tx Power	Sensitivity	Rx Max.
-VT	ST Duplex	MMF	1310nm	-19 ~ -14dBm	-31dBm	-14dBm
-VC	SC Duplex	MMF	1310nm	-19 ~ -14dBm	-31dBm	-14dBm
-VJM	MT-RJ	MMF	1310nm	-19 ~ -14dBm	-31dBm	-14dBm
-VVM	VF-45	MMF	1310nm	-20 ~ -14dBm	-31dBm	-14dBm
-VSA2	SC Duplex	SMF	1310nm	-15 ~ -8dBm	-31dBm	-7dBm
-VSL2	SC Duplex	SMF	1310nm	-15 ~ -7dBm	-32dBm	-3dBm
-VSL3	SC Duplex	SMF	1310nm	-15 ~ -8dBm	-34dBm	0dBm
-VSL4	SC Duplex	SMF	1310nm	-5 ~ 0dBm	-34dBm	-3dBm
-VSL6	SC Duplex	SMF	1310nm	-5 ~ 0dBm	-35dBm	0dBm
-VW3515	Bi-Di SC	SMF	TX 1310nm RX 1550nm	-14 ~ -8dBm	-31dBm	0dBm
-VW5315	Bi-Di SC	SMF	TX 1550nm RX 1310nm	-14 ~ -8dBm	-31dBm	0dBm

MMF : Multimode fiber -62.5/125 μm, 50/125 μm
SMF : Single Mode fiber - 9 /125 μm



FCC Part 15, Class A
CISPR 22 Class A

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-chih, Taipei Hsien, Taiwan.
Tel : 886-2-2698-3878
Fax : 886-2-2698-3873
E-mail : kti@ktinet.com.tw
URL : http://www.ktinet.com.tw

KTI Networks Inc.

7400 Harwin Dr., Suite 120 Houston,
Texas 77036 U.S.A.
Tel : 713-266-3891
Fax : 713-914-0555
E-mail : kti@ktinet.com
URL : http://www.ktinet.com

Trademarks : All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Application

Edge workgroup switch with uplink to 802.1Q tagged backbone network via 1000M fiber

