



KG-500F



1000Base-X Gigabit Ethernet PCI Adapter with SFP Support

Ordering Information :

Model	Fiber Mode	Connector	Ref. Distance
KG-500F-SX	62.5/125 50/125	LC	200m 500m
KG-500F-LX	MM SM	LC	550m 10km

MM : Multimode Fiber
SM : Single Mode Fiber
Ref. Distance: Reference connection distance

Key Features :

- Supports 32-bit 33/66MHz PCI of Rev.2.1/2.2/2.3 specification
- IEEE 802.3z 1000Base-SX/LX compliant
- Provides Tx 8K / Rx 64KB RAM buffer
- Supports full duplex operation up to 2000Mbps data rate over fiber
- Supports full duplex flow control
- Plug-and-Play installation
- Provides LED indicators for easy diagnostic
- Provides SFP to support variety of fiber transceivers
- Complete driver support for most operating systems
- Supports 802.1Q VLAN tagging

Specifications :

Standards	IEEE 802.3z 1000Base-SX/LX
Network Port	SFP for 1000Mbps mini-GBIC fiber transceiver
Host Interface	32-bit 33/66Mhz PCI Rev.2.1/2.2/2.3
LEDs	SFP status, Link status, Optical status
Network Cables	50/125 μ m multimode fiber up to 500m 62.5/125 μ m multimode fiber up to 220m 9/125 μ m single mode fiber
Transfer Rate	Gigabit Ethernet: 2000Mbps (Full-duplex)
Driver Support	Windows XP, 2000, 2003, VistaX32/64, Linux, Netware server
Power Consumption	3.3V/400mA max.
Dimension	130 x 65 mm
Environment	Operation Temperature : 0°C ~50°C Storage Temperature : -20°C ~85°C Relative Humidity : 5%~95%non-condensing
Laser eye safe	IEC 60825-1 Class 1/CDRH Class I
Approval	FCC Class B,CE CISPR22 Class B



FCC Part 15, Class B
CISPR 22 Class B

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-chih, Taipei Hsien, Taiwan.
Tel : 886-2-2698-3878
Fax : 886-2-2698-3873
E-mail : kti@ktinet.com.tw
URL : http://www.ktinet.com.tw

KTI Networks Inc.

7400 Harwin Dr., Suite 120 Houston,
Texas 77036 U.S.A.
Tel : 713-266-3891
Fax : 713-914-0555
E-mail : kti@ktinet.com
URL : http://www.ktinet.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Fiber Optical Specifications :

Model	Connector	Fiber	Wavelength	Tx Power	Sensitivity	Rx Max.	Distance
KG-500F-SX	LC	62.5/125 μ m MMF 50/125 μ m MMF	850nm	-9.5 ~ -4dBm	-18dBm	-1dBm	200m 500m
KG-500F-LX	LC	MMF SMF	1310nm	-9.5 ~ -3dBm	-20dBm	-3dBm	550m 10km

MMF : Multimode fiber 62.5/125 μ m,50/125 μ m
SMF : Single Mode fiber 9 /125 μ m